

GUTEX® Fugendicht Data Sheet



GUTEX Fugendicht, a sealant that comes in a cartridge, is for sealing GUTEX Thermowall/-gf board joints.

Technical Data	GUTEX Fugendicht
Cartridge:	290 ml
Carton contents:	12 cartridges
Shelf life:	18 months
Storage:	Store cool and dry. Avoid exposure to freezing temperatures!
Application temperature:	+ 5 °C to + 40 °C
Thermal stability:	- 40 °C to + 90 °C
Density:	at 23 °C and 50% RH: 1.54 ± 0.03 g/cm ³
Skimming at 23 °C and 50% RH:	Approx. 7 min
Curing:	At 23 °C and 50% RH: After 24 hrs, approx. 2.5 mm After 38 hrs, approx. 3.5 mm
Designation as per EN 15651-1:	F EXT-INT CC 12.5 E
Fire reaction:	E

Composition

- MS polymer hybrid sealant

Applications

- GUTEX Thermowall/GUTEX Thermowall-gf
- With GUTEX Implio® window integration system
- Caulking of joints between insulation boards
- May be applied prior to installation of render coat

Instructions

- The substrate surface must be clean, dry, oil-free and intact.
- Fill joints in their full depth.

Usage Based on 3-mm Bead

Board Thickness in mm Tongue and Groove Boards	Linear Metres/Cartridge
40	~ 6.0
60	~ 4.0
80	~ 3.0
100	~ 2.0

Advantages

- Fast-curing, even at cold temperatures
- Isocyanate-, silicone- and solvent-free
- Superb adhesion to most substrates, including moist surfaces
- Excellent initial adhesion strength
- Virtually odourless, colour-fast, weather- and UV-resistant
- When fully cured, long-lasting elasticity and resistance to ageing

Storage

- Store cool and dry.
- If kept in original packaging, good for 18 months from manufacturing date
- To maintain the best quality until the expiration of the specified shelf life, store this product in its original container. The shelf life expiration date appears in the batch code:

Explanation of batch numbers.:

Digit 1 = final digit of the year, digits 2 & 3 = calendar week

Example: 5450013223 - Shelf life expires with 45th week in 2015

All rights reserved. Henselmann GmbH + Co KG is not liable for any damage resulting from error or misprinting. The technical data provided herein is subject to change. Although all of the information was current at the time of its publication, the publication of superseding

information renders the old information invalid.

The suitability of this product for applications not specified in this data sheet is not guaranteed. Warranty and liability claims are subject to the terms of GUTEX's General Terms of Business.



NATURALLY MADE FROM WOOD