

GUTEX® Mineral-Voranstrich Data Sheet

Primer for final stucco coats that contain organic binders

(A system component in GUTEX Thermowall-plus based composite thermal insulation systems)

Product Features and Advantages	Additional Information
<ul style="list-style-type: none"> – Facilitates bonding of GUTEX Silikonharzputz (silicone resin final coat) to cement and lime based base coats as well as untrowelled, gypsiferous substrates. – Effective primer for the reduction of absorption in highly porous masonry substrates. Water may be used as an alternative. – Reduces absorption of new and old stucco finishes – Resistant to the effects of weather 	<p>Packaging unit: 25 kg disposable tub</p> <p>Storage: If kept properly sealed in the original vessel, the expected shelf-life is 12 months.</p> <p>Transport: No special precautions or instructions necessary.</p> <p>Disposal: Waste, damaged or old material shall be disposed of as specified by applicable law with special care given to the handling of substances designated as hazardous substances.</p> <p>VVS Code: I 610, paints and coatings with aqueous phases</p> <p>Toxicity class: Non-toxic</p> <p>RID/ADR: Non-hazardous</p>
Description and Materials	
GUTEX Mineral Voranstrich is a primer for use with GUTEX Silikonharzputz (silicone resin final stucco coat).	
Binder: Unplasticised copolymer dispersion	
Additives: Selected extenders and pigments	
Applications	
<ul style="list-style-type: none"> – For the regulation of substrate absorption – Priming of unprimed old and new stucco coats – Facilitates bonding 	
Intended area of use: Exterior	
Instructions	
Substrate: The substrate surface must be clean, dry and oil-free. New lime and cement base coats shall be hardened and dry enough to limit alkaline reaction.	
Substrate preparation: Remove dust, dirt and other residues that may prevent effective bonding to the substrate. Remove surface coatings that are not suitable for bonding.	
Application: GUTEX Mineral Voranstrich may be thinned with 15-20% water. Do add foreign additives.	
Equipment cleaning: Clean and rinse with water after use.	
Application temperature: Not for use when colder than 5°C.	
Drying: Subsequent coats may be applied over the primer within approx. 6 hours, depending on overall weather conditions.	
Required quantity: Approx. 0.2 - 0.3 kg/m ²	

All rights reserved. Henselmann GmbH + Co KG shall not be held liable for any damage resulting from error or misprinting. The technical data provided herein is subject to change. Although all of the information herein was up to date at the time of its publication, the publication of superseding information renders the old information invalid. The suitability of this product for applications not specified in this data sheet is not guaranteed. Warranty and liability claims are subject to the terms of Gutex's General Terms of Business.

